

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

865624 LOCTITE GASKET REMOVER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Solvent based cleaner

1.3. Details of the supplier of the safety data sheet

Quest Consumables Ltd
Stock House ,Seymour Road
Nuneaton, Warwickshire
CV11 4LB

Phone: +44 2476 322126

Fax-no.: +44 2476 322117

sales@questconsumables.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable aerosols

Category 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Skin irritation

Category 2

H315 Causes skin irritation.

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Danger

Hazard statement:	<p>H222 Extremely flammable aerosol.</p> <p>H229 Pressurised container: May burst if heated.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p>
--------------------------	---

Precautionary statement:	<p>P251 Do not pierce or burn, even after use.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P102 Keep out of reach of children.</p> <p>***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements***</p>
---------------------------------	--

Precautionary statement:	P261 Avoid breathing spray.
Prevention	

Precautionary statement:	P302+P352 IF ON SKIN: Wash with plenty of water.
Response	P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:
Cleaner

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Methylal 109-87-5	203-714-2	50- < 75 %	Flam. Liq. 2 H225
Propane 74-98-6	200-827-9 01-2119486944-21	10- < 25 %	Flam. Gas 1 H220 Press. Gas H280
1,3-Dioxolane 646-06-0	211-463-5	10- < 25 %	Flam. Liq. 2 H225
Propan-2-ol 67-63-0	200-661-7 01-2119457558-25	3- < 10 %	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336
Ethanol 64-17-5	200-578-6 01-2119457610-43	3- < 10 %	Eye Irrit. 2 H319 Flam. Liq. 2 H225
2-aminoethanol 141-43-5	205-483-3 01-2119486455-28	1- < 2,5 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Corr. 1B H314 Acute Tox. 4; Inhalation H332 Aquatic Chronic 3 H412
Butanone 78-93-3	201-159-0 01-2119457290-43	1- < 2,5 %	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336
Naphtha 64742-48-9	265-150-3 01-2119471843-32	1- < 2,5 %	Asp. Tox. 1 H304 STOT SE 3 H336 Flam. Liq. 3 H226 Aquatic Chronic 3 H412

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to Detergent Regulation 648/2004/EC

15 - 30 % aliphatic hydrocarbons
< 5 % non-ionic surfactants

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation:
Move to fresh air.
Seek medical advice.

Skin contact:
Rinse with running water and soap.
Seek medical advice.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

Do not expose to direct heat.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

Remove sources of ignition.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

Wipe up using absorbent material.

Store in a partly filled, closed container until disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

Keep away from sources of ignition - no smoking.

Vapours should be extracted to avoid inhalation.

Hygiene measures:

- Good industrial hygiene practices should be observed.
- Wash hands before work breaks and after finishing work.
- Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

- Store in a cool, dry place.
- Do not store near sources of heat or ignition, or reactive materials.

7.3. Specific end use(s)

- Solvent based cleaner

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Dimethoxymethane 109-87-5 [DIMETHOXYMETHANE]	1.250	3.950	Short Term Exposure Limit (STEL):		EH40 WEL
Dimethoxymethane 109-87-5 [DIMETHOXYMETHANE]	1.000	3.160	Time Weighted Average (TWA):		EH40 WEL
Ethanol 64-17-5 [ETHANOL]	1.000	1.920	Time Weighted Average (TWA):		EH40 WEL
Propan-2-ol 67-63-0 [PROPAN-2-OL]	500	1.250	Short Term Exposure Limit (STEL):		EH40 WEL
Propan-2-ol 67-63-0 [PROPAN-2-OL]	400	999	Time Weighted Average (TWA):		EH40 WEL
Butanone 78-93-3 [BUTAN-2-ONE (METHYL ETHYL KETONE)]	300	899	Short Term Exposure Limit (STEL):		EH40 WEL
Butanone 78-93-3 [BUTAN-2-ONE (METHYL ETHYL KETONE)]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Butanone 78-93-3 [BUTAN-2-ONE (METHYL ETHYL KETONE)]	200	600	Time Weighted Average (TWA):		EH40 WEL
Butanone 78-93-3 [BUTANONE]	200	600	Time Weighted Average (TWA):	Indicative	ECTLV
Butanone 78-93-3 [BUTANONE]	300	900	Short Term Exposure Limit (STEL):	Indicative	ECTLV
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]	3	7,6	Short Term Exposure Limit (STEL):		EH40 WEL
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]	1	2,5	Time Weighted Average (TWA):		EH40 WEL
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]	3	7,6	Short Term Exposure Limit (STEL):	Indicative	ECTLV
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]	1	2,5	Time Weighted Average (TWA):	Indicative	ECTLV
Paraffin waxes and Hydrocarbon waxes 8002-74-2 [PARAFFIN WAX, FUME]		2	Time Weighted Average (TWA):		EH40 WEL
Paraffin waxes and Hydrocarbon waxes 8002-74-2 [PARAFFIN WAX, FUME]		6	Short Term Exposure Limit (STEL):		EH40 WEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Propan-2-ol 67-63-0	aqua (freshwater)					140,9 mg/L	
Propan-2-ol 67-63-0	aqua (marine water)					140,9 mg/L	
Propan-2-ol 67-63-0	sediment (freshwater)				552 mg/kg		
Propan-2-ol 67-63-0	sediment (marine water)				552 mg/kg		
Propan-2-ol 67-63-0	soil				28 mg/kg		
Propan-2-ol 67-63-0	aqua (intermittent releases)					140,9 mg/L	
Propan-2-ol 67-63-0	STP					2251 mg/L	
Propan-2-ol 67-63-0	oral					160 mg/kg food	
Ethanol 64-17-5	aqua (freshwater)					0,96 mg/L	
Ethanol 64-17-5	aqua (marine water)					0,79 mg/L	
Ethanol 64-17-5	aqua (intermittent releases)					2,75 mg/L	
Ethanol 64-17-5	sediment (freshwater)				3,6 mg/kg		
Ethanol 64-17-5	soil				0,63 mg/kg		
Ethanol 64-17-5	STP					580 mg/L	
Ethanol 64-17-5	oral				720 mg/kg		
Ethanol 64-17-5	sediment (marine water)				2,9 mg/kg		
2-Aminoethanol 141-43-5	aqua (freshwater)					0,085 mg/L	
2-Aminoethanol 141-43-5	aqua (marine water)					0,0085 mg/L	
2-Aminoethanol 141-43-5	aqua (intermittent releases)					0,025 mg/L	
2-Aminoethanol 141-43-5	sediment (freshwater)				0,425 mg/kg		
2-Aminoethanol 141-43-5	sediment (marine water)				0,0425 mg/kg		
2-Aminoethanol 141-43-5	soil				0,035 mg/kg		
2-Aminoethanol 141-43-5	STP					100 mg/L	
Butanone 78-93-3	aqua (freshwater)					55,8 mg/L	
Butanone 78-93-3	aqua (marine water)					55,8 mg/L	
Butanone 78-93-3	aqua (intermittent releases)					55,8 mg/L	
Butanone 78-93-3	STP					709 mg/L	
Butanone 78-93-3	sediment (freshwater)				284,7 mg/kg		
Butanone 78-93-3	sediment (marine water)				284,7 mg/kg		
Butanone 78-93-3	soil				22,5 mg/kg		
Butanone 78-93-3	oral				1000 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Propan-2-ol 67-63-0	Workers	Dermal	Long term exposure - systemic effects		888 mg/kg bw/day	
Propan-2-ol 67-63-0	Workers	Inhalation	Long term exposure - systemic effects		500 mg/m3	
Propan-2-ol 67-63-0	general population	Dermal	Long term exposure - systemic effects		319 mg/kg bw/day	
Propan-2-ol 67-63-0	general population	Inhalation	Long term exposure - systemic effects		89 mg/m3	
Propan-2-ol 67-63-0	general population	oral	Long term exposure - systemic effects		26 mg/kg bw/day	
Ethanol 64-17-5	Workers	Inhalation	Acute/short term exposure - local effects		1900 mg/m3	
Ethanol 64-17-5	Workers	Dermal	Long term exposure - systemic effects		343 mg/kg bw/day	
Ethanol 64-17-5	Workers	Inhalation	Long term exposure - systemic effects		950 mg/m3	
Ethanol 64-17-5	general population	Inhalation	Acute/short term exposure - local effects		950 mg/m3	
Ethanol 64-17-5	general population	Dermal	Long term exposure - systemic effects		206 mg/kg bw/day	
Ethanol 64-17-5	general population	Inhalation	Long term exposure - systemic effects		114 mg/m3	
Ethanol 64-17-5	general population	oral	Long term exposure - systemic effects		87 mg/kg bw/day	
2-Aminoethanol 141-43-5	Workers	Dermal	Long term exposure - systemic effects		1 mg/kg bw/day	
2-Aminoethanol 141-43-5	Workers	Inhalation	Long term exposure - local effects		3,3 mg/m3	
2-Aminoethanol 141-43-5	general population	Dermal	Long term exposure - systemic effects		0,24 mg/kg bw/day	
2-Aminoethanol 141-43-5	general population	Inhalation	Acute/short term exposure - local effects		2 mg/m3	
2-Aminoethanol 141-43-5	general population	oral	Long term exposure - systemic effects		3,75 mg/kg bw/day	
2-Aminoethanol 141-43-5	general population	Inhalation	Long term exposure - local effects		2 mg/m3	
2-Aminoethanol 141-43-5	general population	Inhalation	Long term exposure - systemic effects		2 mg/m3	
Butanone 78-93-3	Workers	Dermal	Long term exposure - systemic effects		1161 mg/kg bw/day	
Butanone 78-93-3	Workers	Inhalation	Long term exposure - systemic effects		600 mg/m3	
Butanone 78-93-3	general population	Dermal	Long term exposure - systemic effects		412 mg/kg bw/day	
Butanone 78-93-3	general population	Inhalation	Long term exposure - systemic effects		106 mg/m3	
Butanone 78-93-3	general population	oral	Long term exposure -		31 mg/kg bw/day	

			systemic effects			
Solvent naphtha (petroleum), heavy aliphatic, low benzene content 64742-48-9	Workers	Dermal	Long term exposure - systemic effects		300 mg/kg bw/day	
Solvent naphtha (petroleum), heavy aliphatic, low benzene content 64742-48-9	Workers	Inhalation	Long term exposure - systemic effects		1500 mg/m ³	
Solvent naphtha (petroleum), heavy aliphatic, low benzene content 64742-48-9	general population	Dermal	Long term exposure - systemic effects		300 mg/kg bw/day	
Solvent naphtha (petroleum), heavy aliphatic, low benzene content 64742-48-9	general population	Inhalation	Long term exposure - systemic effects		900 mg/m ³	
Solvent naphtha (petroleum), heavy aliphatic, low benzene content 64742-48-9	general population	oral	Long term exposure - systemic effects		300 mg/kg bw/day	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Butanone 78-93-3 [BUTAN-2-ONE]	Butan-2-one	Urine	Sampling time: End of shift.		UKEH40BMG V		

8.2. Exposure controls:

Respiratory protection:

Ensure adequate ventilation.

Use only in well-ventilated areas.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filtertype: AX

Filter type: P2

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance

Aerosol

Amber

Odor

Alcoholic

Odour threshold

No data available / Not applicable

pH

10,6 - 11,0

()

Initial boiling point

-44 °C (-47.2 °F)

Flash point	-97 °C (-142.6 °F)
Decomposition temperature	No data available / Not applicable
Vapour pressure	8300 hPa
(20 °C (68 °F))	
Density	0,79 g/cm3
(20 °C (68 °F))	
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	Not miscible
(Solvent: Water)	
Solubility (qualitative)	Miscible
(Solvent: Acetone)	
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	
lower	1,70 %(V)
upper	10,90 %(V)
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	Not available.
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

Ignition temperature 235 °C (455 °F)

SECTION 10: Stability and reactivity

10.1. Reactivity

Strong oxidizing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.
Heat, flames, sparks and other sources of ignition.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

May cause irritation to the digestive tract.

Inhalative toxicity:

May cause irritation to respiratory system.

Skin irritation:

Causes skin irritation.

Solvent may remove essential oils from the skin making it susceptible to attack from other chemicals.

Eye irritation:

Causes serious eye irritation.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Propan-2-ol 67-63-0	LD50	5.338 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity) Expert judgement
Ethanol 64-17-5	LD50	13.700 mg/kg	oral		rat	
2-aminoethanol 141-43-5	LD50	1.515 mg/kg	oral		rat	
Butanone 78-93-3	Acute toxicity estimate (ATE)	2.600 mg/kg	oral			
Butanone 78-93-3	LD50	2.600 - 5.400 mg/kg			rat	OECD Guideline 401 (Acute Oral Toxicity)
Naphtha 64742-48-9	LD50	> 5.000 mg/kg	oral		rat	

Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Propan-2-ol 67-63-0	LC50	72,6 mg/l	Aerosol	4 h	rat	Expert judgement
Ethanol 64-17-5	LC50	124,7 mg/l		4 h	rat	
2-aminoethanol 141-43-5	Acute toxicity estimate (ATE)	1,5 mg/l				
2-aminoethanol 141-43-5	LC50	1 - 5 mg/l	Aerosol	4 h	rat	Expert judgement
Butanone 78-93-3	Acute toxicity estimate (ATE)	5,1 mg/l				
Butanone 78-93-3	LC50	> 5000 ppm		6 h	rat	

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Propan-2-ol 67-63-0	LD50	12.870 mg/kg	dermal		rabbit	Expert judgement
Ethanol 64-17-5	LDLo	20.000 mg/kg	dermal		rabbit	
Ethanol 64-17-5	LD50	15.800 mg/kg				
2-aminoethanol 141-43-5	LD50	1.025 mg/kg	dermal		rabbit	
Butanone 78-93-3	Acute toxicity estimate (ATE)	6.400 mg/kg	dermal			
Butanone 78-93-3	LD50	6.400 - 8.000 mg/kg			rabbit	

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Propan-2-ol 67-63-0	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Ethanol 64-17-5	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-aminoethanol 141-43-5	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Butanone 78-93-3	moderately irritating		rabbit	

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Propan-2-ol 67-63-0	moderately irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Ethanol 64-17-5	Category II		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2-aminoethanol 141-43-5	corrosive		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Butanone 78-93-3	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	
Ethanol 64-17-5	not sensitising	Guinea pig maximisation test	guinea pig	Magnusson and Kligman Method
Butanone 78-93-3	not sensitising	Guinea pig maximisation test	guinea pig	

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Propane 74-98-6	negative with metabolic activation	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Propan-2-ol 67-63-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		
Ethanol 64-17-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	in vitro mammalian chromosome aberration test	without		
2-aminoethanol 141-43-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		Ames Test
2-aminoethanol 141-43-5	negative	oral: feed		mouse	Micronucleus assay
Butanone 78-93-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Propan-2-ol 67-63-0	NOAEL=1500	inhalation	13 weeks6 hours/day, 5 days/week	mouse	
Propan-2-ol 67-63-0	LOAEL=5000	inhalation	13 weeks6 hours/day, 5 days/week	mouse	
Butanone 78-93-3	NOAEL=2500 ppm	inhalation	90 days6 hours/day, 5 days/week	rat	
Butanone 78-93-3	LOAEL=5000 ppm	inhalation	90 days6 hours/day, 5 days/week	rat	

SECTION 12: Ecological information**General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity**Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Methylal 109-87-5	LC50	6.990 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methylal 109-87-5	EC50	> 500 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methylal 109-87-5	EC10	> 500 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,3-Dioxolane 646-06-0	LC50	> 95,4 mg/l	Fish	96 h	Lepomis macrochirus	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,3-Dioxolane 646-06-0	EC50	> 772 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,3-Dioxolane 646-06-0	ErC50	> 877 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	877 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	LC50	9.640 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propan-2-ol 67-63-0	EC50	13.299 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	1.000 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	NOEC	30 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Ethanol 64-17-5	LC50	14.200 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethanol 64-17-5	EC50	9.268 - 14.221 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethanol 64-17-5	EC50	> 5.000 mg/l	Algae	7 d	Scenedesmus quadricauda	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethanol 64-17-5	NOEC	2 mg/l	chronic Daphnia	10 d		
2-aminoethanol 141-43-5	LC50	> 250 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
	NOEC	1.221 mg/l	Fish		Brachydanio rerio (new name: Danio rerio)	OECD 210 (fish early lite stage toxicity test)
2-aminoethanol 141-43-5	EC50	85 mg/l	Daphnia	24 h	Daphnia magna	
2-aminoethanol 141-43-5	NOEC	1 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	EC50	2,5 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-aminoethanol 141-43-5	NOEC	0,85 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Butanone 78-93-3	LC50	3.220 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Butanone	EC50	5.091 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline

78-93-3							202 (Daphnia sp. Acute Immobilisation Test)
Butanone 78-93-3	EC50	> 1.000 mg/l	Algae				OECD Guideline 201 (Alga, Growth Inhibition Test)
Naphtha 64742-48-9	EC50	> 22 - 46 mg/l	Daphnia	48 h	Daphnia magna		OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Naphtha 64742-48-9	NOEC	< 1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata (reported as Raphidocelis subcapitata)		OECD Guideline 201 (Alga, Growth Inhibition Test)

12.2. Persistence and degradability**Persistence and Biodegradability:**

No data available.

Persistence and degradability:**Degradation of surfactants**

The product does not contain surface-active substances as defined in the EU Detergent Regulation (EC/648/2004).

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Methylal 109-87-5			88 %	OECD 301 A - F
1,3-Dioxolane 646-06-0		aerobic	20 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Propan-2-ol 67-63-0	readily biodegradable	aerobic	70 - 84 %	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
Ethanol 64-17-5	readily biodegradable	aerobic	80 - 85 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
2-aminoethanol 141-43-5	readily biodegradable	aerobic	> 80 %	OECD Guideline 301 B (Ready Biodegradability: CO ₂ Evolution Test)
Butanone 78-93-3	readily biodegradable	aerobic	> 60 %	OECD 301 A - F
Naphtha 64742-48-9	readily biodegradable	aerobic	89 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil**Mobility:**

The product evaporates readily.

Bioaccumulative potential:

Does not bioaccumulate.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
1,3-Dioxolane 646-06-0	-0,35					
Propan-2-ol 67-63-0	0,05					OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Ethanol 64-17-5	-0,31					
2-aminoethanol 141-43-5	-1,91				25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Butanone 78-93-3	0,29					

12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
Propane 74-98-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Propan-2-ol 67-63-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Ethanol 64-17-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-aminoethanol 141-43-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Butanone 78-93-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Naphtha 64742-48-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

14 06 03 - other solvents and solvent mixtures

SECTION 14: Transport information**14.1. UN number**

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, flammable

14.3. Transport hazard class(es)

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

14.4. Packaging group

ADR
RID
ADN
IMDG
IATA

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	IMDG-Code: Segregation group 18- Alkalis
IATA	not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content 82,09 %
(1999/13/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapor.
H226 Flammable liquid and vapor.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Label elements (DPD):

F+ - Extremely flammable



Risk phrases:

R12 Extremely flammable.

Safety phrases:

S16 Keep away from sources of ignition - No smoking.
S23 Do not breathe spray.
S24 Avoid contact with skin.
S51 Use only in well-ventilated areas.

Additional labeling:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children

For consumer use only: S2 Keep out of the reach of children.

S46 If swallowed, seek medical advice immediately and show this container or label.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.